

# SERVOPRO Chroma

ULTRA-ACCURATE, HIGHLY VERSATILE TRACE GAS ANALYZER CONFIGURABLE TO A WIDE RANGE OF APPLICATIONS



## SERVOPRO Chroma

The Chroma trace analyzer is one of the most versatile gas monitoring solutions on the market. Utilizing a unique, non-depleting plasma emission detector, the Chroma is a mainframe customized to your application.

Offering multi-component trace measurement at ppb, ppm or % level, the Chroma can monitor H<sub>2</sub>, Ne, O<sub>2</sub>, N<sub>2</sub>, Ar, CH<sub>4</sub>, CO, CO<sub>2</sub> and NMHC impurities in H<sub>2</sub>, O<sub>2</sub>, N<sub>2</sub>, Ar and He. Optimized via a sophisticated and flexible operational software that offers access to all device functions via a PC, the Chroma is configurable for a wide range of complex applications including medical gas purity, air separation, argon recovery, hydrogen purification and semiconductor wafer manufacture.

With a range of sophisticated sensor options supported by PlasmaHC and ArgonSep technology for the measurement of NMHC/methane and separation of argon respectively, many applications will be satisfied by a single 4U rack analyzer configuration: all helping to make the SERVOPRO Chroma one of the most compact and powerful trace analyzers available.

### FLEXIBLE

- Comprehensive solution for ultra-trace H<sub>2</sub>, Ne, O<sub>2</sub>, N<sub>2</sub>, Ar, CH<sub>4</sub>, CO, CO<sub>2</sub> and NMHC in a number of background gases; H<sub>2</sub>, O<sub>2</sub>, N<sub>2</sub>, Ar and He
- Plasma, FID and TCD technologies used depending on application
- Compact design that fits into a single 4U rack
- Flexible communication options including Ethernet and 4-20 mA output

### EASY TO USE

- Comprehensive device interaction and monitoring via intelligent software.
- Full remote configuration via Ethernet/Internet
- Electronic carrier and sample flow PID control system
- Remote range I.D. contact per impurity

### LOW COST OF OWNERSHIP

- Simplified reporting functions facilitated by the software
- PED sensing technology does not require a separate methanizer

### UNRIVALLED PERFORMANCE

- Uses ultra-sensitive and highly selective patented PED sensing technology, delivering the highest reliability and performance currently available
- PlasmaHC measures methane and NMHC without the use of a FID, eliminating the need for maintenance and fuel. ArgonSep separates Ar from O<sub>2</sub> without the need for scrubbers, providing a sensitive, maintenance-free measurement.

### BENCHMARK COMPLIANCE

- Class B digital apparatus requirements of ICES-003 of Canada through the application of EN 61000-6-3:2007
- Part 15 of the US FCC rules for Class B equipment.
- IEC 61010-1 for electrical safety
- EC "Low Voltage Directive" by application of EN 61010-1 and rated for Over Voltage Category II, Pollution Degree 2

Learn more about the SERVOPRO Chroma  
Visit [servomex.expert/pb-chroma](http://servomex.expert/pb-chroma)



SERVOMEX.COM



SERVOMEX  
**ANALYZERS**  
HIGH-PERFORMANCE GAS ANALYSIS

# PRODUCT OVERVIEW: Chroma

## HIGH VERSATILITY FOR DIVERSE APPLICATION NEEDS

Applications that depend on the very highest levels of product purity depend on trace analysis of exceptional sensitivity and performance. Impurities requiring measurement are both diverse in nature and found in a number of background gas streams, so high flexibility is also a must. Measurements need to be reliable, so a technology that can provide stability is essential. No matter what your application monitoring requirements, you'll also want a solution that is easy to use and has a low lifetime cost-of-ownership. We don't believe you should have to compromise.

## A NO COMPROMISE SOLUTION

The Chroma's flexible ultra-trace analysis is delivered through a smart combination of cutting-edge sensing technology and intelligent control software. Benefiting from the fast, accurate, sensitive and selective response of Servomex's non-depleting Plasma Emission Detector (PED) cell, Flame Ionization Detector (FID) and Thermal Conductivity (TCD) technologies, the Chroma offers sophisticated configuration and performance options which are far ahead of the competition.

## EASY AND INTUITIVE TO USE

Added to the Chroma's measurement performance is its ability to provide an easy-to-use solution with added flexibility. Feature-rich software permits full device interaction remotely via Ethernet/Internet, while a full range of reporting options provide simplified statistical data analysis. The Chroma also features a user-friendly high resolution TFT color LCD for easy local configuration and interaction.

## COMPLEMENTARY PRODUCTS

The SERVOPRO Chroma is augmented by complementary products to improve and extend measurement performance.

### SERVOPRO PureGas



SERVOPRO PureGas purifies gases onsite, minimizing gas contamination risk so the Chroma can perform reliably with high levels of sensitivity. Available for Ar and He matrices, the PureGas delivers outlet impurity levels for O<sub>2</sub>, H<sub>2</sub>O, CO, CO<sub>2</sub>, H<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>.

### DF-300



The DF-300 series microprocessor-based analyzer uses Servomex's unique, non-depleting Coulometric E-sensor technology for O<sub>2</sub> measurements at percent, trace and ultra-trace levels.

## KEY APPLICATIONS

- Medical Gas Production
- Medical Gas Verification
- Air separation plants
- Argon purification plants
- Cryogenic truck loading station
- Hydrogen purification plants
- Specialty gas laboratories
- Semiconductor plants
- Helium liquification plants

# PRODUCT DATA: Chroma

OPTIONS	DESCRIPTION	SPECIFICATION
Analog outputs	1 x 4-20 mA output per peak 1 x Isolated mA chromatogram output	Up to 8 outputs High resolution output
Digital outputs	1 x Remote range identification output per peak 2 x Alarm dry contact outputs 1 x System status dry contact output	Up to 8 User pre-settable limited
Digital Input	1 x digital isolated input	Remote initiation of analysis
Solenoid valve	Simple sample and span switching	Dual inlet fitted with a solenoid valve
Sample flow	Simplified sampling	Electronic carrier and sample flow PID control system
PC software	Adds additional dimensions of interaction, reporting and analysis	Facilitates full device interaction including chromatograms and process results obtained via Ethernet or Internet. Can also be used to generate statistics and historical values

## ACCESSORIES

ACCESSORIES AVAILABLE FOR SPECIFIC APPLICATIONS  
- CONTACT YOUR LOCAL SERVOMEX BUSINESS CENTER

MONITORING PERFORMANCE					
Background Gas	H <sub>2</sub>	O <sub>2</sub>	N <sub>2</sub>	Ar	He
Technology * †	Plasma Emission Detector (PED)				
Range	Min 0-1ppm Max 0-500ppm				
Limit of Detection (LOD)	±50ppb or ±1.5% range, whichever is the greater				

\* Flame Ionisation Detector used in selected applications for HC speciation  
 † Thermal Conductivity Detector used in selected applications for high concentration impurities and European Pharmacopeia

BACKGROUND GAS					
Impurities	H <sub>2</sub>	O <sub>2</sub>	N <sub>2</sub>	Ar	He
H <sub>2</sub>	x	•	•	•	•
Ne	•	•	•	x	•
O <sub>2</sub>	x	x	•	•	•
N <sub>2</sub>	•	•	x	•	•
Ar	•	•	•	x	•
CH <sub>4</sub>	•	•	•	•	•
CO	•	•	•	•	•
CO <sub>2</sub>	•	•	•	•	•
NMHC	•	•	•	•	•

• Available x Not Applicable

